

## DIGITUS VGA Splitter 350MHz, 2-Port

DS-41100 4016032325024



**Video Splitter 1 PC, 2 Monitors, 350 MHz**  
**350 MHz, HDSUB 15/M - 2 X HDSUB 15/F, Max. Res. 2048x1536p**

**Provides simultaneous display on two different monitors - Perfect for classrooms, tradeshow, or in-store displays**

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

- 1 Video bandwidth: 350MHz
- 1 Max. resolution: 2048x1536p @60Hz
- 1 DDC, DDC2, DDC2B support
- 1 Cascadable (max. 64)
- 1 Metal housing for better EMI shielding
- 1 Max. transmission distance: 75m
- 1 Video IN/OUT: HD DSUB, 15-pin, jacks

### Package Content

- 1 VGA Splitter 350MHz, 2-port
- 1 Power supply
- 1 Manual
- 1 Support CD-ROM



# DIGITUS VGA Splitter 350MHz, 2-Port

DS-41100 4016032325024



## → Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	7,50	32,00	28,50	32,00	29184,00
Packaging Unit Inside	1	0,75	6,00	25,00	15,00	2250,00
Packaging Unit Single	1	0,75	6,00	25,00	15,00	2250,00
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00

## → Packaging type

Country of origin: China

